








Specification		Type C	
Rated Voltage (AC/DC)		30V (DC)	
Nominal Current		Up to 3A	
Data Transfer Rate		2.0	3.2 Gen1
Plastic / Metal		Plastic	Plastic
STRAIGHT-TO-NON-WATERPROOF SOCKET, Overmolded Double-Ended Cable Assembly, IP68 (Mated)			
⑩ Cable Length: USB 2.0: (A05) 0.5M ~ (005) 5M, USB 3.2 Gen 1: (A05) 0.5M ~ (003) 3M			
	End 1 Type C: Male Connector Male Contact End 2 Non-Waterproof Type A: Male Connector Male Contact	UC20ML-NAML-KA ⑩	UC30ML-NAML-KB ⑩*
	End 1 Type C: Male Connector Male Contact End 2 Non-Waterproof Type C: Male Connector Male Contact	UC20ML-NCML-KA ⑩*	UC30ML-NCML-KB ⑩
STRAIGHT-TO-WATERPROOF SOCKET, Overmolded Double-Ended Cable Assembly, IP68 (Mated)			
⑩ Cable Length: USB 2.0: (A05) 0.5M ~ (005) 5M, USB 3.2 Gen 1: (A05) 0.5M ~ (003) 3M			
	End 1 Type C: Male Connector Male Contact End 2 Type C: Male Connector Male Contact	UC20ML-UCML-KA ⑩*	UC30ML-UCML-KB ⑩*
	End 1 Type C: Male Connector Male Contact End 2 Type C: Female Connector Female Contact	UC20ML-UCFL-KA ⑩*	UC30ML-UCFL-KB ⑩*
STRAIGHT-TO-NON-WATERPROOF SOCKET, Overmolded Double-Ended Cable Assembly, IP68 (Mated)			
⑩ Cable Length: USB 2.0: (A05) 0.5M ~ (005) 5M, USB 3.2 Gen 1: (A05) 0.5M ~ (003) 3M			
	End 1 Type C: Female Connector Female Contact End 2 Non-Waterproof Type A: Male Connector Male Contact	UC20FL-NAML-KA ⑩	UC30FL-NAML-KB ⑩*
	End 1 Type C: Female Connector Female Contact End 2 Non-Waterproof Type C: Male Connector Male Contact	UC20FL-NCML-KA ⑩*	UC30FL-NCML-KB ⑩
STRAIGHT-TO-WATERPROOF SOCKET, Overmolded Double-Ended Cable Assembly, IP68 (Mated)			
⑩ Cable Length: USB 2.0: (A05) 0.5M ~ (005) 5M, USB 3.2 Gen 1: (A05) 0.5M ~ (003) 3M			
	End 1 Type C: Female Connector Female Contact End 2 Type C: Female Connector Female Contact	UC20FL-UCFL-KA ⑩*	UC30FL-UCFL-KB ⑩*

M
a
t
i
n
g

P
a
i
r